



## Redundant PSU

### CRPS R2U 1+1 850W



### Features

- 80 Plus® Platinum
- Active Power Factor  $PF \geq 0.95$
- 0~50 Working Temperature
- Support PMBus 1.2
- Surge: 2KV(L/N-PE) & 1KV(L-N)
- 1+1 Redundant
- Protections: UVP,OVP,OCP,OTP,SCP
- Altitude : 5000M

### Safety

- UL / cUL / TUV / CB

### EMI/EMC

- CE / FCC

### Dimension

- 230 mm (L) x 76 mm (W) x 84 mm (H)

Model	Total Power	Input Type	DC Outputs				
			+3.3 V	+5 V	+12 V	-12 V	+5 Vsb
S2N-851CCP5-B	850 W	100-240 VAC	70.8 A	20 A	20 A	0.5 A	3 A
Regulation			±5 %	±5 %	±5 %	±5 %	±5 %
Ripple & Noise (mVp-p)			120	50	50	120	50

Environmental Specifications	
Operating	20 % ~ 90 % RH non-condensing
Non-Operating	5 % ~ 95 % RH non-condensing
Altitude	5000 Meter

General Specifications	
Hold-up time	12ms @ 115 Vac at 70 % load
Efficiency	Power Module > 94 % @ 50 % load
Protection	OCP, OVP, OTP
MTBF	100,000 hours min. per SR332 at 25 °C

