



REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	CABLE LENGTH
P1 / 24	1	+3.3V	ORANGE	18	MOLEX 39-01-2040 or EQUIV.	650±20mm
	2	+3.3V	ORANGE	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
	5	COM	BALCK	18		
	6	+5V	RED	18		
	7	COM	BALCK	18		
	8	PW-OK	GRAY	24		
	9	+5Vsb	PURPLE	18		
	10	+12V	YELLOW	18		
	11	+12V	YELLOW	18		
	12	+3.3V	ORANGE	18		
	13	+3.3V	ORANGE	18		
	14	-12V	BLUE	24		
	15	COM	BALCK	18		
	16	PS-ON	GREEN	24		
	17	COM	BALCK	18		
	18	COM	BALCK	18		
	19	COM	BALCK	18		
	20	-5V	WHITE	24		
	21	+5V	RED	18		
	22	+5V	RED	18		
	23	+5V	RED	18		
	24	COM	BALCK	18		
P2	1	COM	BALCK	18	MOLEX 39-01-2040 or EQUIV.	650±20mm
	2	COM	BALCK	18		
	3	COM	BALCK	18		
	4	COM	BALCK	18		
P3	1	COM	BALCK	20	MOLEX 39-01-2040 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	COM	BALCK	20		
PA	1	+3.3V	ORANGE	20	MOLEX SD-67926 or EQUIV.	450±15mm
	2	COM	BALCK	20		
	3	+5V	RED	20		
	4	COM	BALCK	20		
PG	1	+12V	YELLOW	20	MOLEX SD-67926 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	+5V	RED	20		
	4	COM	BALCK	20		
PB	1	+3.3V	ORANGE	20	MOLEX SD-67926 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	+5V	RED	20		
	4	COM	BALCK	20		
PC	1	+12V	YELLOW	20	WST P4-AI0202 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	+5V	RED	20		
PD	1	+12V	YELLOW	20	WST P4-AI0202 or EQUIV.	450±15mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	+5V	RED	20		
PE	1	COM	BALCK	20	MOLEX SD-67926 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	+5V	RED	20		
	4	COM	BALCK	20		
PF	1	+12V	YELLOW	20	MOLEX SD-67926 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	+5V	RED	20		
PH	1	+12V	YELLOW	20	WST P4-AI0202 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	+5V	RED	20		
PI	1	+5V	RED	22	AMP 171622-4 or EQUIV.	155±10mm
	2	COM	BALCK	22		
	3	COM	BALCK	22		
	4	+12V	YELLOW	22		

MODEL NO.: TC-1U40PD8UC	TITLE: ASSY	SHEET: 1 OF 1	REV:01
R&D(2)	DRAWN	DATE	
(150.26)	黃淑芳	OCT.21.2019	
INTERIOR COUNTERSIGN:			

NOTE:
 1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
 2. 公差: .XX±0.5 [0.02]、.XXX±0.25 [0.01]

UNIT:mm